

IPEwifi V3

WiFi gateway for IPETRONIK data logger M-LOG V3

- Application for wireless data transfer in WiFi networks
- Access point for Android display systems with IPEmotion App
- FTP data transfer for M-LOG V3
- Configuration via IPEmotion
- 3 LEDs for operation status indication
- Ruggedized diecast aluminium housing



Device	
Voltage supply	9 ... 36 VDC
Power consumption, typical	1.5 W
Working temperature range	-40 ... 85 °C (-40 ... 185 °F)
Storage temperature range	-50 ... 95 °C (-67 ... 203 °F)
IP-Code	IP 54 (ISO 20653 - 2013)
Relative humidity	5 ... 95 %
Dimensions	W126 mm x H50 mm x D25 mm (4.96 in x 1.97 in x 0.98 in)
Weight	165 g (0.36 lb)
Housing material	Diecast aluminium enclosure
Status LED	Orange: WiFi-Verbindung aktiv
Status LED	Orange: LAN-Verbindung aktiv
Status LED	Grün: Versorgung / betriebsbereit
Accessories	
System cable	620-614 620-036
Antenna	IPE-ANT-011 IPE-ANT-004
Kommunikation	
WiFi	2.4 GHz (WiFi 802.11 b/g/n)
WiFi Socket	SMA connector for external antenna